

BS 7835 XLPE / LSZH Medium Voltage 19/33 (36)kV Cable



APPLICATION

Power cables for power networks, underground and in cable ducting, in installations with potential threat to life and equipment in the event of fire, smoke and toxic fumes emissions.

CHARACTERISTICS

Voltage Rating U_0/U (Um)

19/33 (36)kV

Temperature Rating

Fixed: 0°C to +90°C

Minimum Bending Radius

Single core - Fixed: 15 x overall diameter

3 core - Fixed: 12 x overall diameter

(Single core 12 x overall diameter and 3 core 10 x overall diameter where bends are positioned adjacent to a joint or termination provided that the bending is carefully controlled by the use of a former)

STANDARDS

IEC 60502-2, EN 60228

Low Smoke Zero Halogen to: IEC 60754-1/2, IEC 61034-2

Flame Retardant: IEC 60332-3-24 Cat C, IEC 60332-1-2

UV Resistant: ISO 4892-3

Abrasion and Tear Resistant: EN 60229-4.1

Impact rated to: AG2 EN 60364-5.51

THE CABLE TEST

We have world-class testing facility, and made rigorous testing regime, every meter of cable before leaving the factory must go through strict testing, testing qualified products will be shipped to customers, effectively ensure product quality and meet customer requirements.

SUSTAINABILITY COMMITMENT

Guowang Cable actively implements the "carbon reduction" goal, strives to promote the green's low-carbon transformation, strengthens energy-saving and emission reduction technology innovation, and promotes the company's healthy and sustainable development.

CONSTRUCTION

Conductor

Class 2 Stranded Copper Conductor according to BS EN 60228 (previously BS 6360)

Conductor Screen

Semi-conductive XLPE(Cross-Linked Polyethylene)

Insulation

XLPE(Cross-Linked Polyethylene) Type GP8 according to BS 7655

Insulation Screen

Semi-conductive XLPE(Cross-Linked Polyethylene)

Metallic Screen

Individual or collective overall copper tape screen according to BS 7835

Filler

PET (Polyethylene Terephthalate) fibres

Separator

Binding Tape

Bedding

LSZH (Low Smoke Zero Halogen)

Armour

Single core: AWA (Aluminium Wire Armoured)
Multi-core: SWA (Steel Wire Armoured)

Sheath

LSZH (Low Smoke Zero Halogen)

Sheath Colour

● Black

DIMENSIONS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA	NOMINAL DIAMETER mm			NOMINAL WEIGHT
		Under Armour	Over Armour	Overall	
	mm ²				kg/km
1	70	32.6	36.6	41	2300
1	95	34.3	38.3	42.9	2650
1	120	35.9	39.9	44.5	3000
1	150	37.5	42.5	47.3	3500
1	185	39.3	44.3	49.3	4000
1	240	41.7	46.7	51.7	4650
1	300	44.2	49.2	54.4	5450
1	400	47.3	52.3	57.7	6350
1	500	50.5	55.5	61.1	7600
1	630	54.2	59.2	65.0	9150
1	800	60.5	65.5	71.6	11100
1	1000	65	70	76.5	13400
3	50	65.1	71.4	78.2	9150
3	70	68.8	75.1	82.1	10300
3	95	72.6	78.9	86.1	11600
3	120	76.3	82.6	90	12800
3	150	79.3	85.6	93.2	14050
3	185	83.4	89.7	97.5	15650
3	240	88.8	95.1	103.3	18200
3	300	93.9	100.2	108.8	21100
3	400	100.8	107.1	116.1	24200
1	70	32.6	36.6	41	2300

CONDUCTOR

Class 2 Stranded Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA	NOMINAL DIAMETER mm						MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
	Circular		Circular		Circular		Annealed Copper Conductor
	Cu	Al	Cu	Al	Cu	Al	Plain Wires
50	19	19	6	6	6	6	0.387
70	19	19	12	12	12	12	0.268
95	19	19	15	15	15	15	0.193
120	37	37	18	15	18	15	0.153
150	37	37	18	15	18	15	0.124
185	37	37	30	30	30	30	0.0991
240	37	37	34	30	34	30	0.0754
300	61	61	34	30	34	30	0.0601
400	61	61	53	53	53	53	0.047
500	61	61	53	53	53	53	0.0366
630	91	91	53	53	53	53	0.0283
800	91	91	53	53	-	-	0.0221
1000	91	91	53	53	-	-	0.0176

ELECTRICAL CHARACTERISTICS

Current Carrying Capacity

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	CONTINUOUS CURRENT RATING Amps					
		In Ground		In Ducts		In Air	
		Trefoil	Flat	Trefoil	Flat	Trefoil	Flat
1	70	270	280	260	270	310	370
1	95	320	335	305	325	375.000	460
1	120	360	380	340	370	430	530
1	150	410	430	375	410	490	600
1	185	455	485	410	460	550.000	690
1	240	520	560	470	540	650	820
1	300	580	640	500	610	740	940
1	400	650	730	530	690	840	1100
1	500	710	830	570	780	930	1280
1	630	760	940	620	890	1040	1480
1	800	810	1060	660	990	1140	1690
1	1000	860	1170	690	1090	1230	1900
3	50	210	210	180	180	220	220
3	70	250	250	215	215	270	270
3	95	300	300	255	255	330	330
3	120	340	340	290	290	380	380
3	150	380	380	330	330	430	430
3	185	430	430	370	370	490	490
3	240	500	500	430	430	570	570
3	300	540	540	470	470	650	650
3	400	600	600	530	530	740	740
3	240	500	500	430	430	570	570
3	300	540	540	470	470	650	650
3	400	600	600	530	530	740	740

DE-RATING FACTORS

AIR TEMPERATURE °C	25	30	35	40	45	50	55
DE-RATING FACTOR	1.00	0.96	0.92	0.88	0.83	0.78	0.73
GROUND TEMPERATURE °C	10	15	20	25	30	35	40
DE-RATING FACTOR	1.03	1.00	0.97	0.93	0.89	0.86	0.82
GROUND THERMAL RESISTIVITY km/W	0.9	1.0	1.2	1.5	2.0	2.5	3.0
DE-RATING FACTOR	1.06	1.04	1.00	0.92	0.82	0.74	0.68
DEPTH OF LAYING m	0.80	1.00	1.25	1.50	1.75	2.00	2.50
DE-RATING FACTOR	1.00	0.97	0.95	0.94	0.93	0.91	0.90

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.