

Photovoltaic Solar H1Z2Z2-K Cable



APPLICATION

Updated harmonised (H1Z2Z2-K) European standard solar cable intended for the interconnection within photovoltaic systems such as solar panel arrays. Suitable for fixed installations, internal and external, within conduit or systems. Impact tested - Suitable for direct burial. For installations where fire, smoke emissions and toxic fumes create a potential risk to life and equipment. Water resistant to AD8.

CHARACTERISTICS

Voltage Rating U_0/U (Um)

AC: 1000/1000V

DC: 1500/1500V

Maximum Voltage (Umax)

1800V

Test Voltage

6.5kV AC

Temperature Rating

Fixed: -40°C to +90°C

Minimum Bending Radius

5 x overall diameter

Maximum Conductor Temperature

+120°C (for 20000h)

STANDARDS

EN 50618, TÜV 2 PfG 1169/08.2007, EN 50288-3-7, EN 60068-2-78, EN 50395

Flame retardant to IEC/EN 60332-1-2

Low Smoke Zero Halogen to IEC/EN 60754-1/2, IEC/EN 61034-1/2, EN 50267-2-2

Ozone and UV Resistant to EN 60811-403, EN 50396, EN ISO 4892-1/3,

Water Resistant to AD8

THE CABLE TEST

We have world-class testing facility, and made rigorous testing regime, every meter of cable before leaving the factory must go through strict testing, testing qualified products will be shipped to customers, effectively ensure product quality and meet customer requirements.

SUSTAINABILITY COMMITMENT

Guowang Cable actively implements the "carbon reduction" goal, strives to promote the green's low-carbon transformation, strengthens energy-saving and emission reduction technology innovation, and promotes the company's healthy and sustainable development.

CONSTRUCTION

Conductor

Class 5 flexible tinned copper conductor

Insulation

Halogen-free cross-linked compound

Sheath

Halogen-free cross-linked, flame retardant compound

Sheath Colour

● Black

Other colours available on request

DIMENSIONS

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km	TENSILE STRENGTH IN OPERATION N
1	1.5	4.6	36	22
1	2.5	5	46	37
1	4	5.6	62	60
1	6	6.1	82	90
1	10	7.1	125	150
1	16	8.5	190	240
1	25	10.4	285	375
1	35	11.5	385	525
1	50	13.7	540	750
1	70	15.8	740	1050
1	95	17.3	965	1350
1	120	19.1	1210	1800
1	150	21.4	1495	2250
1	185	24.9	1885	2775
1	240	27.3	2395	3600

ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM CONDUCTOR DC RESISTANCE AT 20 °C Ω/km	MAXIMUM CONDUCTOR DC RESISTANCE AT 90 °C Ω/km	CURRENT CARRYING CAPACITY A			VOLTAGE DROP mV/A/m
			Single Cable In Air	Single Cable On Surface	Two Cables Adjacent On Surface	
1.5	13.7	17.468	30	29	24	38.2
2.5	8.21	10.468	41	39	33	23
4	5.09	6.49	55	52	44	14.3
6	3.39	4.322	70	67	57	9.49
10	1.95	2.486	98	93	79	5.46
16	1.24	1.581	132	125	107	3.47
25	0.795	1.013	176	167	142	2.23
35	0.565	0.72	218	207	176	1.58
50	0.393	0.501	276	262	221	1.1
70	0.277	0.353	347	330	278	0.772
95	0.21	0.267	416	395	333	0.585
120	0.164	0.209	488	464	390	0.457
150	0.132	0.168	566	538	453	0.368
185	0.108	0.137	644	612	515	0.301
240	0.0817	0.104	775	736	620	0.228

DDE-RATING FACTORS

AIR TEMPERATURE	UP TO 60°C	70°C	80°C	90°C	100°C	110°C
DE-RATING FACTOR	1.00	0.91	0.82	0.71	0.58	0.41

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.